

UF1 (5dB) Recall Sheet

The recall sheet for the UF1 (5dB) processor is organized into several functional sections:

- EQ Section:**
 - High Shelf:** Five rotary knobs, each with a scale from 1 to 5 dB.
 - High Pass Filter:** Five rotary knobs with frequency scales: 70, 100, 140, 200 Hz; 295, 395, 590 Hz; 750, 1k0, 1k5 Hz; 2k1, 2k8, 4k2 Hz; 5k0, 6k2, 8k7 Hz.
 - Low Pass Filter:** Five rotary knobs with frequency scales: 15, 2.5, 4, 6 Hz; 1.0, 0.7, 0.5 Hz; 0.3, 0.15 Hz.
- Phase Section:**
 - phase L:** A rotary knob with a scale from 0 to 10 dB.
 - L+R:** A rotary knob with a scale from 0 to 10 dB.
 - side:** A rotary knob with a scale from 0 to 10 dB.
- Stereo Width Section:**
 - stereo-width:** A rotary knob with a scale from 0.5 to 1.5.
 - M/S:** A rotary knob with a scale from 0 to 2.
- Mode Section:**
 - mode:** A selector with options: St-MS, St-St, off, MS-St, MS-MS.
 - cut-off:** A selector with options: off, 30 Hz, 38 Hz.
- Control Section:**
 - focus:** Five rotary knobs, each with a scale from 0.3 to 15.
 - solo:** Five rotary knobs, each with a scale from 0.3 to 15.
 - off:** Five rotary knobs, each with a scale from 0.3 to 15.
 - prefade:** A rotary knob with a scale from 0 to 10.
 - link solo:** A rotary knob with a scale from 0 to 10.

Artist:

Date:

Project:

Session:

Track:

Studio:

Instrument:

Engineer:

Version:

Assistant:

Notes: